




TECHNICAL DATA SHEET

Type no.		P60 09	
Type no.		013560090101	
Standards		DIN EN 50342, DIN IEC 60095-2	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		60 Ah (K20)	
Cold start current		540 A (EN)	
Dimensions and weights			
Box	T5		
Length max.	241mm		
Width max.	175mm		
Box height max.	175mm		
Total height max.	175mm		
Battery weight	Ca. 15,0 kg (+/- 5 %)	Symbolpicture	
Electrolyte density		Approx. 1,28 kg/l	
Elektrolyt		Diluted sulphuric acid	
Items/pallet		72	
Pallet ID		Euro palett	
Items per layer		18	
Features			
Base hold-down		B13	
Layout		0	
Terminal		1	
Separator		PE bag separator	
Degassing		Battery with central degassing	
Flame arrester		Available	
Maintenance ¹⁾			
Water consumption		< 1g/Ah	
Refill water		Distilled or demineralised (DIN 43530)	
Self-discharge		Approx 3 % per month	
Charging current		Approx 1/10 of the rated capacity	
Charging voltage ²⁾		max. 14,8 V	

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge

Document DBTBAT00132 prepared on 2015-04-01; Rights relating to changes and errors retained.
original